



VTB Quiet Click Plank

Product Specifications

Style Name	VTB Quiet Click Plank
Style Number	All Wood
Construction	Heavy Commercial VTB Core
Class / ASTM F 1700	Class I Printed Film Vinyl Tile, Type A (smooth), Type B (embossed)
Wear layer Thickness	20 mil or (0.5mm)
Overall Thickness	5.5 mm
Nominal Dimensions	Plank 7.25" wide x 48" long
Actual Size / ASTM F 536	Width: 7.25" or 184.15mm, Length: 48" or 1219.2mm
Backing Class	Recycled Commercial Grade EVA
Finish	GlobalTECH-Enhanced Urethane
Added Antimicrobial	Yes
Installation	Floating
Recommended Adhesive	N/A

Packaging

Square Feet per Carton	23.51 Sq. feet Plank
Pieces per Carton	10 pcs plank
Weight per Carton	40 lbs

Testing

Slip Resistance / ASTM D 2047	>0.80
Residual Indentation / ASTM F970	2200 psi
Flexibility / ASTM F 137	Passes
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM F 925	Passes
Radiant Flux / ASTM 648	Passes, >0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E 662	Passes, <450

Warranty

10 year limited commercial wear warranty.

Please visit www.f2cfloor.com for the most current warranty information.

Environmental

Indoor Air Quality	FloorScore certified
LEED Scorecard	MR4, IEQ4.1, IEQ4.3