



VTB Wood Veneer Click

Product Specifications

Style Name	VTB Wood Veneer Click
Style Number	All Wood
Construction	Heavy Commercial VTB Core Real Wood Veneer
Class / ASTM F 1700	(embossed)
Wear layer Thickness	1.2 mm Wood Veneer
Overall Thickness	8.7 mm
Nominal Dimensions	Plank 6" wide x 48" long
Actual Size / ASTM F 536	Width: 6" or 152.40mm, Length: 48" or 1219.2mm
Backing Class	Recycled Commercial Grade EVA
Finish	Enhanced Urethane
Added Antimicrobial	NO
Installation	Floating
Recommended Adhesive	N/A

Packaging

Square Feet per Carton	19.70 Sq. feet Plank
Pieces per Carton	10 pcs plank
Weight per Carton	52 lbs

Testing

Slip Resistance / ASTM D 2047	>0.80
Residual Indentation / ASTM F970	2200 psi
Flexibility / ASTM F 137	Passes
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM F 925	Passes
Radiant Flux / ASTM 648	Passes, >0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E 662	Passes, <450

Warranty

5 year limited commercial wear warranty.
Please visit www.f2cfloor.com for the most current warranty information.

Environmental

Indoor Air Quality	FloorScore certified
LEED Scorecard	MR4, IEQ4.1, IEQ4.3