



WoodStock

Product Specifications

Style Name	WoodStock
Style Number	All Wood
Construction	Heavy Commercial Luxury Vinyl Tile
Class / ASTM F 1700	Class I Printed Film Vinyl Tile, Type A (smooth), Type B (embossed)
Wear layer Thickness	20 mil or (0.5mm)
Overall Thickness	3.0 mm (.120")
Nominal Dimensions	Plank 6" wide x 36"
Actual Size / ASTM F 536	Length: 36" or 914.4 mm
Backing Class	Recycled three ply fused Commercial Grade
Finish	WoodStock-Enhanced Urethane
Added Antimicrobial	Yes
Installation	Glue Down
Recommended Adhesive	TechDesign 400

Packaging

Square Feet per Carton	36 Sq. feet
Pieces per Carton	Plank 18 pcs
Weight per Carton	Plank 40 lbs

Testing

Slip Resistance / ASTM D 2047	>0.80
Residual Indentation / ASTM F970	1100 psi
Flexibility / ASTM F 137	Passes
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM F 925	Passes
Radiant Flux / ASTM 648	Passes, >0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E 662	Passes, <450

Warranty

10 year limited commercial wear warranty.

Please visit www.f2cfloor.com for the most current warranty information.

Environmental

Recycled Content	Post-consumer – 43.30% Pre-consumer – 33.70%
Indoor Air Quality	FloorScore certified
LEED Scorecard	MR4, IEQ4.1, IEQ4.3