



Plankit LVT Specifications

Plank size: 7 x 48



SPECIFICATION

CONSTRUCTION	Luxury Vinyl Tile with iGuard Surface	
PLANK SIZE	EN ISO 24346	185x1220 mm
THICKNESS	EN ISO 24346	2.5 mm
WEAR LAYER	EN ISO 24340	0.55 mm
TOTAL WEIGHT	EN ISO 23997	3.8 kg/m²

CLASSIFICATION

BINDER CONTENT	EN ISO 10582	Type I.
EUROPEAN CLASSIFICATION	EN ISO 10582	class: 33/42
RESIDUAL INDENTATION	EN ISO 24343	max. 0.1 mm
DIMENSIONAL STABILITY	EN ISO 23999	max. 0.25 %
CURLING	EN ISO 23999	max. 2 mm

PERFORMANCE

ABRASION GROUP	MSZ EN 660-1	class: T
FIRE RESISTANCE	EN 13501-1	class: Bfl-s1
SLIP RESISTANCE	EN 13893	DS
ELECTRICAL PROPERTIES	EN 1815	max. 2 kV / Antistatic
THERMAL RESISTANCE	ISO 8302	0.014 m²K/W
LIGHT FASTNESS	EN ISO 105-B0	grade 6
CHEMICAL RESISTANCE	EN ISO 26987	✓
	ASTM F925	✓
HYGENIE	bacterial resistant	
CASTOR CHAIR RESISTANCE	EN 425 / ISO 4918	✓
ENVIRONMENTAL ATTRIBUTES	solvent and phtalathe free	
SURFACE TREATMENT	iGuard PUR Surface / Easy cleaning	
CONTENT OF PCP	EN 12673	does not contain
FORMALDEHIDE EMISSION	ENV 717-1	E1 (no emission)
VOC		pass
CE MARKING	EN 14041	✓

